§ 234.311

(4) Have white text set on a blue background with a white border, except that the U.S. DOT National Crossing Inventory number may be black text set on a white rectangular background.

§ 234.311 ENS sign placement and maintenance.

- (a) Number of signs at highway-rail or pathway grade crossing. (1) In general. The maintaining railroad, or the railroad appointed pursuant to \$234.306(b), for a highway-rail or pathway grade crossing shall place and maintain a sign on each approach to the crossing that conforms to \$234.309, except as provided in paragraph (a)(2) of this section.
- (2) Exceptions. (i) At a farm grade crossing, the responsible railroad shall place and maintain a minimum of one sign that conforms to §234.309 at the crossing.
- (ii) At a railroad yard, or a port or dock facility that does not meet the definition of "plant railroad" in §234.5, the responsible railroad shall place and maintain a minimum of one sign at each vehicular entrance to the yard, or the port or dock facility in accordance with §234.309, in lieu of placing signs at each crossing within the yard, or the port or dock facility. Each sign must be placed so that it is clearly visible to a driver of a motor vehicle located at the vehicular entrance to the yard, or the port or dock facility.
- (b) Placement of sign(s). (1) Each sign required by paragraph (a) of this section must be located at the crossing, except as provided in paragraph (a)(2)(ii) of this section, and maintained by the responsible railroad so that the sign—
- (i) Is conspicuous to users of the roadway or pathway by day and night;
- (ii) Does not obstruct any other sign or traffic control device at the crossing;
- (iii) Does not limit the view of a train approaching the highway-rail or pathway grade crossing; and
- (iv) If mounted on a post, has supports that are crashworthy (*i.e.*, breakaway or yielding).
- (2) A sign placed on the signal bungalow does not comply with paragraph (b)(1)(i) of this section.

(c) Repair or replacement of ENS sign. If an ENS sign required by this subpart is discovered by the responsible railroad to be missing, damaged, or in any other way unusable to vehicular or pedestrian traffic, the responsible railroad shall repair or replace the sign no later than 30 calendar days from the time of detection.

[77 FR 35191, June 12, 2012, as amended at 78 FR 16423, Mar. 15, 2013]

§234.313 Recordkeeping.

- (a) In general. Each railroad subject to this subpart shall keep records in accordance with this section. Records may be kept either on paper forms provided by the railroad or by electronic means in a manner that conforms with §234.315. Each dispatching railroad responsible for receiving reports pursuant to §234.303(a), each third-party telephone service responsible for receiving reports pursuant to §234.307, and, if applicable, each maintaining railroad shall keep, at a minimum, the following information for each report received under this subpart:
- (1) The nature of the reported unsafe condition;
- (2) The location of the highway-rail or pathway grade crossing, by highway name, if applicable, and the U.S. DOT National Crossing Inventory number.
- (3) The time and date of receipt of the report by the railroad:
- (4) If applicable, whether the person who provided the report was a railroad employee, law enforcement officer, highway traffic official, or other employee of a public agency acting in an official capacity;
- (5) Actions taken by the railroad prior to resolving the reported unsafe condition at the grade crossing (e.g., warning train crews, notifying the maintaining railroad, or contacting law enforcement or other public authorities):
- (6) If the reported unsafe condition is substantiated, actions taken by the railroad to remedy the reported unsafe condition, if lawful and feasible;
- (7) The time and date when the reported unsafe condition was remedied:
- (8) If no remedial action was taken, the reason why; and
- (9) If a dispatching railroad, in accordance with §234.305, is required to